


Strip Light Comparison

KEY



White Lumens: 100, 2500, 5000, 7500, 10000
 Color Function, Dimmable, Environmental Rating

Model	Icons	Power	Sizes	White Lm/ft	lm/W @ 24 V	White Lumens	Color Function	Dimmable	Environmental Rating
WLS15		12 or 24 V DC	6 (220–1200 mm)	350	73	350-1400	Single Dual 	✓	IP66 IP67
WLS15H		24 V DC	4 (360–1200 mm)	750	110	750-3000	Single	✓	IP66 IP67
WLS28-2		12 to 30 V DC	8 (145–1130 mm)	800	110	800-3200	Single Dual Multi 	✓	IP65 IP67 IP69K
WLS27		12 to 30 V DC	8 (145–1130 mm)	800	110	800-3200	Single Dual Multi 	✓	IP65 IP67 IP69K
WLB32		12 to 30 V DC 90 to 264 V AC	4 (285–1130 mm)	750	100	750-3000	Single	Rocker switch for 0/50/100% option	IP50
WLS70		12 to 30 V DC 100 to 277 V AC	4 (300–1200 mm)	1350	146	1350-5400	Single	✓	IP65
WLB72		90 to 264 V AC	2 (1200 & 2400 mm)	1700	132	4225-8350 (inspection models) 6800-13600 (basic models)	Single	✓	IP20
WLB92		12 to 30 V DC 90 to 264 V AC	2 (550 & 1100 mm)	1755	109	3510-7150	Single	✓	IP40