Sensor Array Bar Replacement Window



Datasheet

The SABRW is a replacement window for the diffuse model Sensor Array Bar. Replacement windows are available in the lengths listed below. The replacement window attaches using the pre-installed adhesive tape.

Replacement Window Model	Sensor Length	Window Material	Material Thickness
SABRW998P	998 mm	Polycarbonate 1	1.5 mm (0.06 in)

Install the Replacement Window

- 1. Loosen the end cap without the cable entry.
 - This will help to remove the old window and help install the new one.
- 2. Remove the damaged window and all residue from the housing window channel.
- 3. Using a soft cloth, clean the metal surfaces on both sides of sensor' window channel. Clean the sensor lens, if needed.
- 4. Peel the paper backing from the tape.
 - The adhesive tape is pre-installed to the window.
- Press one end of the window to the cable end of the sensor housing, and apply pressure as you move slowly to the other end.
- Press window down firmly moving along the entire length, using 103 kPa (15 psi) of pressure for best adhesion to the housing.
- 7. Re-tighten the end-cap to about 0.5N-M (4 inch-lbs).
- 8. Peel away the protective coating from the window's outer surface.

Maintain the Replacement Window

To prevent loss of excess gain, clean the windows when they become dirty. Remove dirt and/or oil from the front face of the window using a mild detergent or window cleaner and a soft cloth. Avoid industrial cleaning agents or cleaning agents containing alcohol, as they may damage the window material or the sensor. Replace the window if it is damaged or scratched in an area directly over the sensors.

Banner Engineering Corp. Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LABILITY, NEGLIGENCE, OR OTHERWISE.

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

For diffuse model Sensor Array Bars only

Original Document 212926 Rev. A